


ANSTRUDE

	Origin	Yonne; France
	Petrographic classification	Sedimentary rocks - biochemical sedimentary rocks - Oolite (EN 12670)
	Appearance	Olitic limestone with beige colored, practically smooth background, with a fine to medium gray grain.
	Alternative names	

Usage

General	The stone and surface finish should be selected depending on the intended use.	
Applications		
Recommendations		
	<div style="background-color: black; color: white; text-align: center; padding: 2px;">Internal Applications</div> <ul style="list-style-type: none"> - Inside Paving - Wall cladding - Decorative cut-to-size - Stairs 	<div style="background-color: black; color: white; text-align: center; padding: 2px;">Outdoor Applications</div> <ul style="list-style-type: none"> - Facade cladding

Hardness (Mohs)	Weight	Water absorption	Porosity
			
3	2100 kg/m ³	NPD*	21,5 %
	EN 1936		EN 1936
Compressive strength	Flexural strength	Wear resistance	FROSt RESISTANCE
			
49 Mpa	6,0 MPa	38,5 mm	NPD*
EN 1926	EN 12372	EN 14157	

NPD*: geen technische gegevens beschikbaar - no technical data available - pas d' informations techniques disponibles

ANSTRUDE

Observations and recommendations

- Shades of color and / or granulometry may be present between the different batches and even within the same batch.
- Veins and / or fossils may appear due to geological formation. These are not technical defects and they are part of the material.
- Due to the mineralogical composition, this material is not resistant to acids.
- This material can not be polished because of its geological composition. Other finishes are possible, the surface then gets a different structure, design or color.
- Small holes may appear on the surface of this natural stone. This is an intrinsic characteristic of the material which can therefore not be subject to claims. These holes may be clogged during the re-grouting of the slabs.

Installation

General
Installation system
Joint Width

General procedures of good workmanship should be followed when laying the tiles (cfr. BBRI: Belgian Building & Research Institute ref. 137 Guide for Installing - Natural Stone and ref. 213). Immediately after delivery, the material will be stored indoors or at least protected from rain, wind and frost. If slabs are damaged or broken, the supplier must be informed before installation. They will then be used, as far as possible, against walls or for certain cuts.

Before installation, the installer will examine the slabs (previously dried) with the client and / or the architect to check for any deviations from the samples. The slabs will be carefully mixed before laying, in order to obtain a harmonious distribution of colors and various shades of the material.

Important: "Installation means acceptance!", It means that AFTER the installation, no more claims will be possible, except for hidden defects.

<table style="width: 100%; border-collapse: collapse;"> <tr style="background-color: black; color: white; text-align: center; padding: 5px;"><td>Flooring Inside</td></tr> <tr style="padding: 5px;"><td>The tiles will be laid on a dry screed using a flex glue such as Beltraflex or a ready-to-use white mortar for natural stones. In the case of installation with underfloor heating, it is advisable to strictly follow the supplier's instructions (see also the brochures of the BBRI - TI 179 and 189).</td></tr> </table>	Flooring Inside	The tiles will be laid on a dry screed using a flex glue such as Beltraflex or a ready-to-use white mortar for natural stones. In the case of installation with underfloor heating, it is advisable to strictly follow the supplier's instructions (see also the brochures of the BBRI - TI 179 and 189).	<table style="width: 100%; border-collapse: collapse;"> <tr style="background-color: black; color: white; text-align: center; padding: 5px;"><td>Exterieur Flooring</td></tr> <tr style="padding: 5px;"><td style="text-align: center;">Not suitable for outdoor paving</td></tr> </table>	Exterieur Flooring	Not suitable for outdoor paving
Flooring Inside					
The tiles will be laid on a dry screed using a flex glue such as Beltraflex or a ready-to-use white mortar for natural stones. In the case of installation with underfloor heating, it is advisable to strictly follow the supplier's instructions (see also the brochures of the BBRI - TI 179 and 189).					
Exterieur Flooring					
Not suitable for outdoor paving					

3 - 5 mm (sawn edges)

;

Maintenance

General
First cleaning
Regular maintenance
Protection
Recommendations

For more information on maintenance, see the document entitled "Care instructions" (available from us). We recommend that you follow these instructions so as not to damage the stone. The products used must be suitable for the materials. Follow the manufacturer's advice. In general, it must be stated that no moisture may be exaggerated when maintaining natural stone!

First cleaning with a suitable cleaning agent (eg Lithofin Multi-Cleaner - note: does not contain acid) applicable one week after rejoining the floor. If a cement veil should appear, use the same product combined with a single-disc machine.

Use for regular maintenance a product suitable for natural stone, such as Lithofin Wash & Clean. In order to better protect the surface finish, we advise to treat it periodically (1 to 2 times per month) with a nourishing product for natural stone, such as Lithofin Care-Sheen.

When the floor is completely dry we strongly recommend to protect sensitive areas (kitchen, bathroom, etc.) with a suitable sealer (e.g. Lithofin MN Stain Stop ECO).

Do not use any acid-based products for the maintenance of this natural stone.