



## TERRAZZO BASALT GREY

	<b>Origin</b>	Italy
	<b>Petrographic classification</b>	Blended Material - cement based terrazzo
	<b>Appearance</b>	Terrazzo composed of marble granules, cement and color pigments in different proportions.
	<b>Alternative names</b>	

### Usage

<b>General</b>	<p>The stone and surface finish should be selected depending on the intended use.</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: 1px solid black; padding: 5px;"> <div style="background-color: black; color: white; text-align: center; padding: 2px;"><b>Internal Applications</b></div> <ul style="list-style-type: none"> <li>- Inside Paving</li> <li>- Wall cladding</li> <li>- Decorative cut-to-size</li> <li>- Stairs</li> </ul> </td> <td style="width: 50%; border: 1px solid black; padding: 5px;"> <div style="background-color: black; color: white; text-align: center; padding: 2px;"><b>Outdoor Applications</b></div> <p style="text-align: center;">not suitable for external applications</p> </td> </tr> </table>		<div style="background-color: black; color: white; text-align: center; padding: 2px;"><b>Internal Applications</b></div> <ul style="list-style-type: none"> <li>- Inside Paving</li> <li>- Wall cladding</li> <li>- Decorative cut-to-size</li> <li>- Stairs</li> </ul>	<div style="background-color: black; color: white; text-align: center; padding: 2px;"><b>Outdoor Applications</b></div> <p style="text-align: center;">not suitable for external applications</p>
<div style="background-color: black; color: white; text-align: center; padding: 2px;"><b>Internal Applications</b></div> <ul style="list-style-type: none"> <li>- Inside Paving</li> <li>- Wall cladding</li> <li>- Decorative cut-to-size</li> <li>- Stairs</li> </ul>			<div style="background-color: black; color: white; text-align: center; padding: 2px;"><b>Outdoor Applications</b></div> <p style="text-align: center;">not suitable for external applications</p>	
<b>Applications</b>				
<b>Recommendations</b>				

Hardness (Mohs)	Weight	Water absorption	Porosity
			
NPD*	2600 kg/m <sup>3</sup>	< 4,0 %	NPD*
		EN 13748-1	
Compressive strength	Flexural strength	Wear resistance	FROSt RESISTANCE
			
NPD*	> 8,6 MPa	14,5 cm <sup>3</sup> / 50 cm <sup>2</sup>	NPD*
	EN 13748-1	EN 13748-1	

NPD\*: geen technische gegevens beschikbaar - no technical data available - pas d' informations techniques disponibles

### Observations and recommendations

<ul style="list-style-type: none"> <li>- In case of excessive contact with water, this material will discolor and / or peel off locally.</li> <li>- This material is composed of a variation of rock fragments with possible various characteristics, such as hardness or resistance to acids.</li> <li>- Due to the mineralogical composition, this material is not resistant to acids.</li> <li>- Shades of color and / or granulometry may be present between the different batches and even within the same batch.</li> <li>- Small pits and / or hairline cracks can sometimes occur with this material.</li> </ul>
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

# TERRAZZO BASALT GREY

## Installation

<b>General</b>
<b>Installation system</b>
<b>Joint Width</b>
<b> </b>

General procedures of good workmanship should be followed when laying the tiles (cfr. BBRI: Belgian Building & Research Institute ref. 137 Guide for Installing - Natural Stone and ref. 213). Immediately after delivery, the material will be stored indoors or at least protected from rain, wind and frost. If slabs are damaged or broken, the supplier must be informed before installation. They will then be used, as far as possible, against walls or for certain cuts.

Before installation, the installer will examine the slabs (previously dried) with the client and / or the architect to check for any deviations from the samples. The slabs will be carefully mixed before laying, in order to obtain a harmonious distribution of colors and various shades of the material.

Important: "Installation means acceptance!", It means that AFTER the installation, no more claims will be possible, except for hidden defects.

Flooring Inside	Exterieur Flooring
<p>For floor and wall applications, an adapted glue has to be used on a dry sub-surface (counter-floor).</p>	<p>Not suitable for outdoor paving</p>

3 - 5 mm (sawn edges)

;When using silicones for filling joints between pieces, take care that the compound stone surface is well protected with tape, since traces of silicones are hard to remove.;;

## Maintenance

<b>General</b>
<b>First cleaning</b>
<b>Regular maintenance</b>
<b>Protection</b>
<b>Recommendations</b>

For more information on maintenance, see the document entitled "Care instructions" (available from us). We recommend that you follow these instructions so as not to damage the stone. The products used must be suitable for the materials. Follow the manufacturer's advice. In general, it must be stated that no moisture may be exaggerated when maintaining natural stone!

First cleaning with a suitable cleaning agent (eg Lithofin Multi-Cleaner - note: does not contain acid) applicable one week after rejoining the floor. If a cement veil should appear, use the same product combined with a single-disc machine.

For regular maintenance, it is important not to use greasy products to avoid the formation of a superficial greasy layer.

When the floor is completely dry we strongly recommend to protect sensitive areas (kitchen, bathroom, etc.) with a suitable sealer (e.g. Lithofin MN Stain Stop ECO).

Do not use any acid-based products for the maintenance of this natural stone.